



Submittal Data Sheet: PTAC-12K-12D(43)

UNIT



PTAC-12K-12D(43)

ACCESSORIES

(Each Sold Separately)

- WALL SLEEVE
- STAMPED GRILLE
- ARCHITECTURAL GRILLE
- SUB BASE
- THERMOSTAT
- WIRELESS CONTROL
- MOTION CONTROL

Dimensions & Weight Indoor Unit		
Dimensions of Main Unit W x H x D	In.	42 x 16.0 x 21.5
Dimensions of Wall Sleeve W x H x D	In.	42 x 16 x 13.75"
Weight-Net	lbs.	108.0
Weight-Gross	lbs.	132.3
R410A Refrigerant Charge	lbs.	1.67

Job Name:		Tag #:	
Location		Date:	
Engineer:		Approval:	
Submitted to:		Unit #:	
Submitted by:		Drawing #:	
Reference		PO #:	

The HARMONY STANDARD features touch pad controls, a digital display, that provides precise climate control, so your guests can customize their comfort level. Two efficient direct-drive motors power an outdoor condensing cool fan, and a 3 speed cross-flow random pitch indoor blower engineered to deliver cooling and heating evenly throughout any room.

Models 265-277 / 1 / 60		PTAC-12K-12D(43)	
Cooling Capacity (Rated)	Btu/h		11800 / 12000
Heating Capacity (Rated)	Btu/h		-
Cooling Power Input	W		1120 / 1120
Heating Power Input	W		-
Cooling Power Current	Amp		5.3 / 5.1
Heating Power Current	Amp		-
Rated Input (Without/With Ele. Heater)	W		1394 / 3000
Rated Current (Without/With Ele. Heater)	Amp		7.57 / 14.4 - 13.0
Rated Ele. Heater	KW		3
MCA	Amp		18.6
Recommended Circuit Breaker HVAC	Amp		20
Air Flow Rate (H/M/L)	CFM		320 / 295 / 280
Fresh Air Ventilation	CFM		up to 60
Dehumidifying Volume	Pints/day		65.9373
EER	Btu/h.w		10.5 / 10.7
COP	WW		-
Reference Only-Good for Floor Space, of Mild Load, in Residential Applications	Sq. Ft		160-240
Isolation			I
Moisture Protection			IP24
Allowed Maximum Operation Pressure-High Side	PSI		550
Allowed Maximum Operation Pressure-Low Side	PSI		290
Indoor Side	Fan Type		Cross-flow
	Fan Wheel Dia. x Length	In.	4.8 x 27.8
	Fan Motor Speed(H/M/L)	RPM	1100 / 1000 / 920
	Output of Fan Motor	W	23
	Fan Motor RLA	Amp	0.36
	Fan Motor Capacitor	UF	1
	Input of Heater	W	2452 / 3000
	Evaporator Form		Aluminum Fin-Copper Tube
	Pipe Diameter	In.	9/32
	Row-FPI		3x 18
	Coil Length (WxHxD)	In.	27.5 x 9.53 x 1.5
	Fuse	Amp	3.15
	Sound Pressure Level (H/M/L)	dB (A)	53 / 52 / 51
	Sound Power Level (H/M/L)-	dB (A)	63 / 62 / 61
Outdoor Side	Compressor Type		Rotary
	L.R.A.	Amp	29.5
	Compressor RLA	Amp	5
	Compressor Power Input	W	1125
	Overload Protector		B245-140K-141H
	Metering Device		Capillary
	Panel Continued	°F	61 - 86
	Outdoor Ambient Temp (Cooling)	°F	55 - 115
	Outdoor Ambient Temp (Heating)	°F	≤75
	Condenser		Aluminum Fin-Copper Tube
	Form Pipe Diameter	In.	7/32
	Rows-FPI		3x 18
	Coil Length (W x H x D)	In.	25 0 x 13.5 x 0.9
	Fan Motor Speed	RPM	1370
Output of Fan Motor		65	
Fan Motor RLA	Amp	0.67	
Fan Motor Capacitor	UF	2.5	
Fan Type		Axial-flow	
Fan Diameter	In.	13.75	
Sound Pressure Level (H/M/L)	dB (A)	63 / 61 / 59	
Sound Power Level (H/M/L)	dB (A)	73 / 71 / 59	




Submittal Data Sheet: PT AC-12K-12D(43)

UNIT

Dimensions (inches)	
W	42"
H	16"
D	21 1/2"

SLEEVE

Dimensions (inches)	
SW	42"
SH	16"
SD	13 3/4"



FEATURES

- 208-230 / 1 / 60 power input
- 20 Amp LCDI Cord
- Quiet and efficient heating & cooling.
- Tactile Display shows set temperature & operating modes.
- Two motors quietly and powerfully distribute air evenly.
- Fresh Air damper allows selection of air source
- Dip Switches for easy configuration
- Preheating coil prevents cold air blowing at start up.
- Wide working ambient temperature ranges
- Fan blade design aides in evaporating condensate
- Stylish Design
- Impact resistant ABS cover
- Steel Frame with Powder Coated Components
- Fits a Standard PTAC Opening
- Built to UL/CSA/AHRI standards
- Easy installation and maintenance



Touch Pad Control with Digital Display




Main Control Board



Washable and Reusable Particulate Air Filter



Condensate Anti-freeze Drainage Valve



Energy Management & Thermostat Connections

YMGI Group
 601 Arrow Ln, O'Fallon, Missouri 63366
 Phone: 1-866-833-3138
 Fax: 1-866-377-3355
 ymgigroup.com

Sales Representative or Distributor: