



Submittal Data Sheet: WMMP-09K-31A(P4)

SYSTEM



WMMS-09K-31A(P4)



ACCESSORIES

- WIRED OR WIRELESS THERMOSTAT
- REMOTE NETWORK CONTROL
- LCDI PLUG
- HOODED INTAKE/EXHAUST COVERS

MODEL NO.	WMMS-09K-34A(P4)	
Precharged Refrigerant		R410A
Min. Wiring Size length ≤15 FT	AWG	14
HVAC Circuit Breaker	AMP	20
Open Stripped End Wire		3 Ft.
LCDI Plug		OPTIONAL
Round Intake/Exhaust Diameter	in.	8"
Maximum Exhaust Air Pipes Length	ft.	25 ft.
Limit High (Top to Ground)	ft.	8
Limit Low (Top to Ground)	ft.	0
Air-Flow Pipes		1 intake / 1 exhaust
Grilles		1 intake / 1 exhaust
Net/Gross Weight	lbs	104 / 112
Dimensions W x H x D	in.	37 x 24 x 10

Job Name:		Tag #:	
Location		Date:	
Engineer:		Approval:	
Submitted to:		Unit #:	
Submitted by:		Drawing #:	
Reference		PO #:	


The HARMONY STANDARD features touch pad controls, a digital display, that provides precise climate control, so your guests can customize their comfort level. Two efficient direct-drive motors power an outdoor condensing cool fan, and a 3 speed cross-flow random pitch indoor blower engineered to deliver cooling and heating evenly throughout any room.

MODEL NO.	WMMS-09K-31A (P4)	
THERMAL MODE		AC Only
COOLING CAPACITY Rated ID 80/67 °F OD 95 °F	BTU/H	9000
HEATING CAPACITY Rated ID 70/60 °F OD 47 °F (17 °F)	BTU/H 1 (2)	N/A
ELECTRIC HEATER	WATTS	N/A
DEHUMIDIFICATION	PTS./DAY	42.2
SEER	BTU/H.W	13
HSPF	BTU/H.W	N/A
SOUND LEVEL (POWER) INDOOR/OUTDOOR	dB(a)	22-23 / 36-38
INPUT POWER SOURCE	V / Ph / Hz	A: 115 / 1 / 60 F: 220 / 1 / 50
POWER CONSUMPTION COOLING	WATTS	960
POWER CONSUMPTION HEATING	WATTS	N/A
TOTAL CURRENT COOLING	AMP	8.9
TOTAL CURRENT HEATING	AMP	N/A
MCA	AMP	15
HVAC CIRCUIT BREAKER	AMP	20
INDOOR FAN	TYPE	CROSS-FLOW
	CFM	230 / 265 / 300
INDOOR MOTOR	RATED WATTS	14 - 15
	MAX. SPEED	1350
OUTDOOR FAN	TYPE	CENTRIFUGAL
	CFM	1175
OUTDOOR MOTOR	STYLE	PSC
THERMOSTAT CONTROL	REPLACING PCB	OPTIONAL
REMOTE CONTROL	INCLUDED	Yes
LOW AMBIENT CONTROL	INCLUDED	Yes
DEFROST ON DEMAND	INCLUDED	Yes
ANTI-ICE		ID/OD
WORKING AMBIENT TEMPERATION RANGES AC / HP	°F	45-104 / NA



OUTDOOR UNIT

Dimensions (inches)	
W	37"
H	24"
D	10"



FEATURES

- 208-230 / 1 / 60 power input
- Quiet and efficient heating & cooling.
- Display shows set temperature & operating modes.
- Motorized louver system quietly distributes air evenly
- "U-TOUCH" Remote Control.
- DC Inverter technology
- Wide working ambient temperature ranges
- Reusable Washable Filters
- Stylish Design
- Durable all metal construction
- Installs with just 2 8" holes for intake and exhaust
- Built to ETL/UL/CSA/ARI standards
- Easy installation and maintenance

YMGI Group
601 Arrow Ln, O'Fallon, Missouri 63366
Phone: 1-866-833-3138
Fax: 1-866-377-3355
ymgigroup.com
sales@ymgigroup.com

Sales Representative or Distributor: