



Submittal Data Sheet: WMMS-18K-V2B(58)4

INDOOR UNIT



WMMS-18E-V2B(58)4

OUTDOOR UNIT



WMMS-18C-V2B(58)4

ACCESSORIES

- ADVANCED HEALTHY KIT
 - HEPA/Enzyme/Cold Catalyst Filter
 - Anion Generator
- THERMOSTAT
- MOUNTING BRACKETS
- FOOT RISERS
- COPPER/WIRE/ACC.SET
- LINESET COVERS
- WINTER WIND BAFFLE
- BRIDGE CONTROLLER

Job Name:		Tag #:	
Location		Date:	
General Contractor:		Mechanical Contractor:	
Sales Representative:		Sales Engineer:	
Submitted by:		Drawing #:	
Reference		PO #:	

YMGI's ductless Wall Mount Mini Split (WMMS) is designed for high performance, easy installation and servicing. The single-zone WMMS system consists of 1 wall-mounted indoor unit and 1 outdoor unit. The outdoor unit is designed for horizontal venting, making condenser installation in tight areas simple. Ideal for multi-family and high-rise buildings in residential, commercial, institutional, and industrial applications. Includes U-Touch remote control.



System		WMMS-18K-V2B(58)4
Power Supply	V/Ph/Hz	208-230 / 1 / 60
Power Voltage Allowed Min./Max.	V	187 / 253
Surge Protector In Incoming Power Supply	Field-Install	Recommended
Cooling Capacity	Btu/h	6800 / 18000 / 20000
Heating Capacity Min./Rating/Max.	Btu/h	7300 / 19800 / 23500
Cooling Power Input Min./Stand./Max.	W	450 / 1435 / 2150
Heating Power Input Min./Stand./Max.	W	580 / 1730 / 2600
EER	W/W	3.68
EER	(Btu/h)/w	12.50
COP	W/W	3.35
COP	(Btu/h)/w	11.45
SEER		20
HSPF		10
Cooling Current	A	6.37
Heating Current	A	7.68
Rated Input	W	3000
Rated Current	A	10.39
Rated Heating Current	A	12.56
Max. Over Current Protection	A	30
Min. Current (MCA)	A	16
Indoor Unit Model		WMMS-18E-V2B(58)4
Fan Diameter Length (DxL)	inch	ø4 3/16 × 27 5/16
Cooling Speed	r/min	1400 / 1200 / 1050 / 800
Heating Speed	r/min	1400 / 1200 / 1100 / 900
Air Flow Volume	CFM	560 / 490 / 410 / 330
Dehumidifying Volume	pt/day	3.80
Fan Motor Power Output	W	60
Fan Motor RLA	A	0.24
Fuse on Control Board	A	3
Evaporator Form		Aluminum Fin-Copper Tube
Fuse Current	A	3.15
Set Temperature Range	°F	61-86
Sound Pressure Level	dB (A)	47/43/40/39
Sound Power Level	dB (A)	57/53/50/49
Outdoor Unit Model		WMMS-18C-V2B(58)4
Compressor Brand		GR
Compressor Oil		RB68EP
Compressor Type		Rotary
Compressor LRA.	A	25
Compressor RLA	A	12.08
Compressor Power Input	W	1440
Compressor Overload Protector		1NT11L-6233 or KSD115°C or HPC115/95U1
Fan Type / Diameter	--/inch	Axial-flow / 21.654
Fan Motor Power Output	W	60
Fan Motor RLA	A	0.49
Outdoor Unit Air Flow Volume	CFM	1880
Condenser Fin / Tube Structure		Aluminum Fin-copper Tube
Maximum Allowable Pressure	PSIG	624
Throttling Method		Electron expansion valve
Defrosting Method		Automatic Defrosting
Sound Pressure / Power Level	dB (A)	55 / 65
Cooling Operation Ambient Temp. Range	°F	0-115
Heating Operation Ambient Temp. Range	°F	-4-75
R410A Refrigerant Factory Charge	ozs	56.44
Factory Charge for Pipe Length	ft.	24.6
Gas Additional Charge	oz/ft.	0.2

System		WMMS-18K-V2B(58)4
Dimensions & Weight Indoor Unit		
Indoor Unit Model		
WMMS-18E-V2B(58)4		
Dimension (WxHxD)	inch	38 3/16 × 11 13/16 × 8 13/16
Dimension of Package (LxWxH)	inch	40 31/32 × 15 5/64 × 12 19 / 32
Net/Gross Weight	lbs	27.6 / 34.2
Dimensions & Weight Outdoor Unit		
Outdoor Unit Model		
WMMS-18C-V2B(58)4		
Dimension of Unit (WxHxD)	Inch	37.63 × 27.63 × 15.63
Dimension of Package (WxHxD)	Inch	40.5 × 29.63 × 18
Net / Gross Weight	lbs	106 / 116
Connection Pipes		
Factory Charge for Pipe Length	ft.	24.6
Gas Additional Charge	oz/ft.	0.2
Outer Diameter of Liquid Valve	inch	1/4"
Outer Diameter of Gas Valve	inch	5/8"
Max Elevation Difference IDU-ODU	ft.	32.8
Max Copper Line Length	ft.	80




OUTDOOR UNIT

Dimensions (inches)	
W	37.63"
H	27.63"
D	15.63"




INDOOR UNIT


Dimensions (inches)	
W	38 3/16"
H	11 13/16"
D	8 13/16"



MOUNTING PLATE



TERMINAL BLOCK



FEATURES

- 208-230/1/60 power input
- Quiet and efficient heating & cooling.
- LED display shows set temperature & operating modes.
- Motorized louver system quietly distributes air evenly
- "U-TOUCH" Remote Control.
- DC Inverter technology
- Wide working ambient temperature ranges
- Stylish design
- Compact outdoor unit with side discharge
- Outdoor unit ships pre-charged.
- World-class quality compressors
- Durable powder coated cabinet
- Default flare brass connection valves
- Knock-outs for refrigerant pipes and wires
- Built to ETL/UL/CSA/ARI standards
- Easy installation and maintenance

YMGI Group

601 Arrow Ln, O'Fallon, Missouri 63366
 Phone: 1-866-833-3138
 Fax: 1-866-377-3355
 ymgigroup.com

Sales Representative or Distributor: